

LUX-CM630-277-42

LUXX 630W CMH 120-277V TECHNICAL SPECIFICATIONS



Physical

Ballast Length	180mm 7.1"
Ballast Width	280mm 11"
Ballast Height	105mm 4.1"
Hood Length	356mm 14"
Hood Width	356mm 14"
Total Length	680mm 26.9"
Total Weight	7.56 16.44lbs

Performance

Input Voltage	120 / 208 / 240 / 277V
120V	5.56A
208V	3.20A
220V	3.10A
240V	2.80A
277V	2.40A
Input Current	5.56 / 3.2 / 2.8 / 2.4A
Input Power	686W
Min Power Factor	>95%
THD	<15%
Power Cord	10ft
120V	NEMA 5-15P (10ft)
208-240V	NEMA 6-15P (10ft)
277V	NEMA L7-15P (10ft)


Performance Requirements

Rated Mains Voltage	120-277V
Mains Frequency	50/60Hz
Operational Frequency	140-220Hz
Voltage Range	108-305V

Luxx 630w CMH | Distance From Canopy: 2' | 4x4 Footprint

122				341				130
	220			560				240
		468		910		460		
			731	901	742			
208	332	648	715	787	766	650	363	222
			700	839	715			
		478		957		504		
	250			685			273	
144				402				126

Average PPFD = 562.7



Wavelength (NM) | Luxx 315 CMH 4200k

